

Muskol Aerosol 23.5% DEET

Version 1.0

Revision Date 03/01/2017

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product information Product Name: SDS Number: UI Number:

Muskol Aerosol 23.5% DEET 122000014179 1612370

Use

: Insect-repellent

Company Bayer Inc. 2920 Matheson Boulevard East Mississauga, ON L4W 5R6 CANADA (800) 622-2937

In case of emergency: Chemtrec: (800) 424-9300 CANUTEC: (613) 996-6666

2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

Classification according to national GHS implementation:

Flammable aerosols, Category 1 (H222) Skin irritation, Category 2 (H315) Eye irritation, Category 2A (H319)

Label elements

Labelling according to national GHS implementation:



Danger

Hazard statements:

H222 Extremely flammable aerosol. H315 Causes skin irritation. H319 Causes serious eye irritation.

Precautionary statements:

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ eye protection/ face protection.

Muskol Aerosol 23.5% DEET

122000014179 Print Date 03/01/2017

Version 1.0

Revision Date 03/01/2017

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Other hazards

Other hazards which do not result in classification: None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

This product is a mixture.

Hazardous components

N,N-Diethyl-m-toluamide

Concentration [Weight percent] 24 CAS-No.: 134-62-3 CAS name: Benzamide, N,N-diethyl-3-methyl-

GHS Classification:



Acute Tox. 4 H302 Eye Irrit. 2 H319 Skin Irrit. 2 H315

Ethanol Concentration [Weight percent] 44 CAS-No.: 64-17-5 CAS name: Ethanol

GHS Classification:



Flam. Liq. 2 H225

Propane Concentration [Weight percent] 10 CAS-No.: 74-98-6 CAS name: Propane

GHS Classification:



Isobutane Concentration [Weight percent] 7.6 CAS-No.: 106-97-8 CAS name: Butane Flam. Gas 1 H220 Press. Gas Liquef. Gas H280



Muskol Aerosol 23.5% DEET

Version 1.0

Revision Date 03/01/2017

GHS Classification:



Flam. Gas 1 H220 Press. Gas Liquef. Gas

Isobutane Concentration [Weight percent] 3.2 CAS-No.: 75-28-5 CAS name: Propane, 2-methyl-

GHS Classification:



Press. Gas Liquef. Gas H280 Flam. Gas 1 H220

For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

Description of first aid measures

General advice: No hazards which require special first aid measures.

If inhaled: If symptoms persist, call a physician.

In case of skin contact: If skin irritation persists, call a physician.

In case of eye contact: Flush eyes with water as a precaution.

If swallowed: Not an expected entry route.

Most important acute symptoms/effects

Indication of any immediate medical attention and special treatment needed

5. FIREFIGHTING MEASURES

Extinguishing media

Suitable extinguishing media: Any

Special hazards arising from the substance or mixture

Specific hazards during firefighting: Fire may cause evolution of: Carbon monoxide (CO) Carbon dioxide (CO2)

Further information: Prevent fire extinguishing water from contaminating surface water or the ground water system.

Advice for firefighters

Special protective equipment for firefighters: In the event of fire, wear self-contained breathing apparatus.

Muskol Aerosol 23.5% DEET

Version 1.0

Revision Date 03/01/2017



6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Use adequate ventilation. Keep people away from and upwind of spill/leak.

Environmental precautions

Methods and materials for containment and cleaning up

Methods for cleaning up: Suppress (knock down) gases/vapours/mists with a water spray jet. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Place in closed containers. Label for proper disposal.

Reference to other sections

Additional advice: Keep away from/remove sources of ignition. Possible need to alert the neighbourhood.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling:

Use adequate ventilation.

Take measures to prevent the build up of electrostatic charge. Keep away from open flames, hot surfaces and sources of ignition.

Conditions for safe storage, including any incompatibilities

Specific end use(s)

8. EXPOSURE CONTROLS/PERSONAL PROTECTION Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Ethanol	64-17-5	TWA	1,000 ppm 1,880 mg/m3	CA AB OEL
		STEL	1,000 ppm	CA BC OEL
		TWAEV	1,000 ppm 1,880 mg/m3	CA QC OEL
Propane	74-98-6	TWA	1,000 ppm	CA AB OEL
		TWA	1,000 ppm	CA BC OEL
		TWAEV	1,000 ppm 1,800 mg/m3	CA QC OEL
		TWA	1,000 ppm	CA ON OEL
Isobutane	106-97-8	TWA	1,000 ppm	CA AB OEL
		TWA	600 ppm	CA BC OEL
		STEL	750 ppm	CA BC OEL



Muskol Aerosol 23.5% DEET

sion 1.0	0 /0 D		evision Date 03/01	/2017	122000014 Print Date 03/01/2	
			TWAEV	800 ppm 1,900 mg/m3	CA QC OEL	
Isobutane		75-28-5	TWA	1,000 ppm	CA AB OEL	
			TWA	1,000 ppm	CA BC OEL	
			TWA	800 ppm	CA ON OEL	
Personal protective equi	pment					
Respiratory protection	:	Recommended Filter type: HEPA				
		None requi	red for consume	er use of this product.		
Hand protection Material	:	Chemically resistant gloves.				
Remarks	:	None required for consumer use of this product.				
Eye protection	:	Safety glasses None required for consumer use of this product.				
Protective measures	:	Wear suitable protective equipment. Please consult label for end-user requirements.				

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Form: Colour: Odour: Melting point/range: Boiling point/boiling range: Density:	aerosol colourless, to, yellowish Alcohol No statements available. 79 - 100 ℃ at 1,013 hPa ca. 0.75 - 0.79 g/cm³ at 20 ℃ at 1,013 hPa
Bulk density:	No statements available.
Vapour pressure:	3,100 - 3,790 hPa at 20 °C
Viscosity, dynamic:	No statements available.
Viscosity, kinematic:	No statements available.
Flow time:	No statements available.
Surface tension:	No statements available.
Water solubility:	No statements available.
Solubility(ies):	No statements available.
pH:	No statements available.
Corrosive to metal:	No statements available.
Partition coefficient	Ethanol
(n-octanol/water):	log Pow: -0.320



Muskol Aerosol 23.5% DEET

Version 1.0

Revision Date 03/01/2017

	Isobutane log Pow: 2.9
Auto-flammability:	422 °C
Flash point:	13 $^{ m C}$ Information refers to the main component.
Inflammability (solid, gaseous):	No statements available.
Explosion limits:	Ethanol upper: 15 %(V) lower: 3.5 %(V)
	Propane upper: 10.8 %(V) lower: 1.7 %(V)
	Isobutane upper: 9.4 %(V) lower: 1.4 %(V)
	upper: 9.4 %(V) 231 mg/m³ lower: 1.5 %(V) 37 mg/m³
Other information	

Miscibility with water:

No statements available.

10. STABILITY AND REACTIVITY

Reactivity No statements available.

Reactions with water / air: No statements available.

Ignition temperature: Ethanol

425 °C

Propane

470 ℃ DIN 51794

Isobutane

365 ℃ DIN 51794

460 ℃ DIN 51794

Burning number: No statements available.

Chemical stability

Thermal decomposition: No data available

Dust explosion characteristic number: No statements available.

Dust explosion class:

Muskol Aerosol 23.5% DEET

Version 1.0

Revision Date 03/01/2017

122000014179 Print Date 03/01/2017

Not applicable

Impact sensitivity:

No data available

Hazardous reactions:

No data available

Explosive properties:

No statements available.

Possibility of hazardous reactions

deflagration ability: No statements available.

Smoldering combustion: No statements available.

Conditions to avoid Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 122F (50 C).

Minimum ignition energy: No data available

Oxidizing properties: No statements available.

Incompatible materials

Materials to avoid: Oxidizing agents

Hazardous decomposition products Carbon monoxide (CO), Carbon dioxide (CO2)

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute oral toxicity	:	Acute toxicity estimate (ATE): 4,875 mg/kg Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate (ATE): > 5,000 mg/kg Method: Calculation method
Components:		
N,N-Diethyl-m-toluamide:		
Acute oral toxicity	:	LD50 (Mouse): 1,170 mg/kg

Assessment: Harmful if swallowed.



Muskol Aerosol 23.5% DEET

Version 1.0

Ethanol:	
Acute oral toxicity :	LD50 (Rat): 10,470 mg/kg Method: OECD 401 Assessment: No adverse effect has been observed in acute toxicity tests.
Acute inhalation toxicity :	LC50 (Rat): 124.7 mg/l, ca. 65360 ppm Exposure time: 4 h Method: OECD 403 Assessment: The substance or mixture has no acute inhalation toxicity
Acute dermal toxicity :	LD50 (Rabbit): 15,800 mg/kg Assessment: No adverse effect has been observed in acute toxicity tests.
Propane:	
•	Assessment: No adverse effect has been observed in acute toxicity tests.
Acute inhalation toxicity :	Symptoms: Daze, Suffocation Assessment: The substance or mixture has no acute inhalation toxicity
Acute dermal toxicity :	Assessment: No adverse effect has been observed in acute toxicity tests.
Isobutane:	
Acute inhalation toxicity :	LC50 (Rat): 65.8 mg/l Exposure time: 4 h Assessment: The substance or mixture has no acute inhalation toxicity

Skin corrosion/irritation

Components:

N,N-Diethyl-m-toluamide: Assessment: Causes skin irritation.

Ethanol:

Species: Rabbit Method: OECD Test Guideline 404 Result: No skin irritation

Propane:

Remarks: Rapid evaporation of the liquid may cause frostbite.

Muskol Aerosol 23.5% DEET

Version 1.0

Revision Date 03/01/2017



Serious eye damage/eye irritation

Components:

N,N-Diethyl-m-toluamide:

Assessment: Causes serious eye irritation.

Ethanol:

Species: Rabbit Result: Eye irritation Method: OECD 405

Propane:

Remarks: Rapid evaporation of the liquid may cause frostbite.

Respiratory or skin sensitisation

Components:

Ethanol:

Test Type: Skin sensitisation Species: Guinea pig Method: Local lymph node test (LLNA) Result: Does not cause skin sensitisation.

Assessment:	An acute toxic effect is not expected.	
Propane:		
Assessment:	An acute toxic effect is not expected.	
Germ cell mutagenicity		
Components:		
Ethanol:		
Genotoxicity in vitro	: Test Type: Ames test Species: Salmonella typhimurium Method: OECD 471 Result: negative	
	: Test Type: Mouse lymphoma assay Method: OECD 476 Result: negative	
Genotoxicity in vivo	: Test Type: Chromosome aberration test in vivo Species: Mouse Method: OECD 478 Result: ambiguous	
	Test Type: Micronucleus test Species: Mouse Method: OECD 474	
	Page 9 of 13	

Muskol Aerosol 23.5% DEET

Version 1.0

Revision Date 03/01/2017



Result: negative

Components:

Ethanol:

Repeated dose toxicity -	:	An acute toxic effect is not expected.
Assessment		

Propane:

Repeated dose toxicity -	:	An acute toxic effect is not expected.
Assessment		

Further information

Components:

Ethanol:

Remarks: Breathing of the fumes may lead to narcotic symptoms.

Remarks: If inhaled: headaches Vomiting Nausea

Remarks: After absorption of large quantities hypotension coma Unconsciousness respiratory paralysis

12. ECOLOGICAL INFORMATION

EcotoxicityComponents:N,N-Diethyl-m-toluamide:Ecotoxicology Assessment
Chronic aquatic toxicity:Harmful to aquatic life with long lasting effects.Ethanol:
Toxicity to fish:LC50 (Leuciscus idus (Golden orfe)): 8,140 mg/l
Exposure time: 48 hToxicity to daphnia and other
aquatic invertebrates:EC50 (Daphnia magna (Water flea)): 9,268 - 14,221 mg/lToxicity to algae::Toxic limit concentration (Scenedesmus quadricauda (Green
algae)): 5,000 mg/l



Muskol Aerosol 23.5% DEET Version 1.0

Version 1.0		Revision Date 03/01/2017	122000014179 Print Date 03/01/2017
Toxicity to bacteria	:	Toxic limit concentration (Pseudomonas putida): 6,500 mg/l
Ecotoxicology Assessmen Acute aquatic toxicity		slightly water endangering	
Propane:			
Ecotoxicology Assessmen Acute aquatic toxicity		This product has no known ecotoxicological eff	ects.
Persistence and degradabi	lity		
<u>Components:</u> Ethanol:			
Biodegradability	:	Result: rapidly biodegradable	
Bioaccumulative potential			
Components:			
Ethanol:			
Bioaccumulation	:	Remarks: Bioaccumulation is unlikely.	
Partition coefficient: n- octanol/water	:	log Pow: -0.320	
Isobutane:			
Bioaccumulation	:	Remarks: Low potential for bioaccumulation	
Partition coefficient: n- octanol/water	:	log Pow: 2.9	
Mobility in soil			
No data available			
Other adverse effects			
Product:			
Additional ecological information	:	Do not allow to enter surface waters or ground	water.

13. DISPOSAL CONSIDERATIONS

Disposal methods Waste from residues : If discarded in its purchased form, this product would not be a hazardous waste either by listing or by characteristic. However, under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material Page 11 of 13

Muskol Aerosol 23.5% DEET

122000014179 Print Date 03/01/2017

Version 1.0

Revision Date 03/01/2017

containing the product or derived from the product should be classified as a hazardous waste.

14. TRANSPORT INFORMATION

<u>Sea transport (IMDG)</u> UN Number Description of the goods Class IMDG-Labels Marine pollutant	1950 AEROSOLS 2.1 2.1 no
<u>Air transport (IATA)</u> UN Number Description of the goods Class Dangerous goods labels Environmentally hazardous	1950 AEROSOLS, FLAMMABLE 2.1 2.1 no
<u>Land transport TDG</u> UN Number Description of the goods Class Dangerous goods labels	1950 AEROSOLS 2.1 2.1

15. REGULATORY INFORMATION

The components of this product are reported in the following inventories:DSLAll components of this product are on the Canadian DSL

Canadian lists

Marine pollutant

No substances are subject to a Significant New Activity Notification.

no

16. OTHER INFORMATION

Full text of H-Statements mentioned in chapters 2 and 3

- H220 Extremely flammable gas.
- H222 Extremely flammable aerosol.
- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.

SAFETY DATA SHEET Muskol Aerosol 23.5% DEET

122000014179 Print Date 03/01/2017

Version 1.0

Revision Date 03/01/2017

Further information

Revision Date : 03/01/2017

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.